

# NEW! Mini Monitor by Point Source Audio



(ACTUAL SIZE)

PSA Model#  
**SPOT-01N**

The SPOT-01N Mini Monitor is an extremely compact, passive loudspeaker able to provide coverage where space is limited. Measuring a mere 4", this 16-ohm speaker has a power handling of 100W which can provide the gap coverage to amplify speech or sound in practically any venue.

Exclusively from  
**Wider Pro**

SPOT-01N delivers as its name implies! The versatility for fill and spot coverage is endless for including **front/side fill, over/under balconies, and spot monitoring.**

## SPECIFICATIONS

Transducer: One 4" Cone Driver  
Impedance: 16 Ohms  
Power Handling: 100w RMS, per EIA RS-426-A  
Sensitivity: 1w1m 86 dB, Measured with Pink Noise in Half Space  
Frequency Response: 145 Hz to 11k Hz  $\pm 3$  dB, -10 at 105 Hz  
Max Continuous SPL: 106 dB  
Max Peak SPL: 112 dB  
Dynamic Range: 100 dB  
Phase Response: 200 Hz to 12 kHz  $\pm 45^\circ$   
Coverage: 90° Horizontal and Vertical  
Weight: 3.6 lbs (1.6 kg)  
Dimensions: 4.75"D x 4.25"W 4.25"H (120mm x 108mm x 108mm)  
Depth Includes Rear Connector  
Accessory: Mounting Bracket (Sold Separately)

Copyright 2019 WiderPro

## TOP OR SIDE MOUNTING CONFIGURATIONS



AVAILABLE AT

**WIDER**

widerpro.com